

Message

Sent: 3/5/2019 8:09:57 PM
To: Dan Johnson [DanJohnson@florencecopper.com]
CC: Albright, David [Albright.David@epa.gov]
Subject: RE: M57-O Replacement Well

Hi Dan,

Your proposed design estimated top of bedrock at 545 ft and the top of the screen 70 ft below that. Your top of bedrock is higher than expected. Your top of the screen should be consistent with 60-70 ft below the top

Nancy Rumrill (rumrill.nancy@epa.gov)
Drinking Water Protection Section (WTR-3-2)
US EPA, Region IX
75 Hawthorne St.
San Francisco, CA 94105
Phone (415) 972-3293

From: Dan Johnson <DanJohnson@florencecopper.com>
Sent: Tuesday, March 5, 2019 7:05 AM
To: Rumrill, Nancy <Rumrill.Nancy@epa.gov>
Cc: Albright, David <Albright.David@epa.gov>
Subject: M57-O Replacement Well

Good Morning Nancy,

We're in accordance M57-O Replacement Well Work Plan but I wanted to keep EPA informed on the construction of the M57-O Replacement Well. Based on the attached log, we note the following observations and propose the following top of screen for well M57-O-R.

Log Indications:

- The lithologic log reflects bedrock at a depth of 460 ft.
- The Gamma log kicks strongly at a depth of 450 ft.
- The 16 and 64-inch resistivity kick strongly at a depth between 480 and 485 ft.
- These log indications are consistent with the separation between the gamma and resistivity kicks we have seen at other borings.

We propose that we use the deepest of the log indications to pick the top of bedrock, at a depth of 485 feet bgs. Consequently, we propose that the top of screen be placed no higher than 525 feet bgs.

Please let me know if you or your consultants have any concerns about our proposed well construction.

Dan Johnson VP | General Manager



Florence Copper Inc.

1575 W. Hunt Highway Florence AZ USA 85132
C 520-233-1930 T 520-374-3984 F 520-374-3999
E danjohnson@florencecopper.com Web florencecopper.com

"Notice Regarding Transmission

This message is intended only for the person(s) to whom it is addressed and may contain information that is privileged and confidential. If you are not the intended recipient, you are hereby notified that any dissemination or copying of this communication is prohibited. Please notify us of the error in communication by telephone (770-373-4533) or by return e-mail and destroy all copies of this communication. Please note that any views or opinions presented in this email are solely those of the author and do not necessarily represent those of Taseko Mines Limited or any affiliated or associated company. The recipient should check this email and any attachments for the presence of viruses. Neither Taseko Mines Limited nor any affiliated or associated company accepts any liability for any damage caused by any virus transmitted by this email. Thank you."